

TECHNICAL DATA SHEET

MONTACK PROFESIONAL

Product description

Polychloroprene-based adhesive in organic solvents modified with rosin resins, tackifiers, additives and inorganic bulking agents

Montack Profesional is specially formulated to secure all types of materials on different substrates, both indoors and outdoors, providing high final strength.

Technical characteristics

Appearance	Thixotropic cream-coloured paste with characteristic odour	
Density	approx. 1.18	kg/l
Dry residue	57 – 58	%
Sag (Daniels)	less than 1mm	
Tensile strength	approx. 100 kg/cm ²	48 hr.
Service temp.	-20 to +110	°C
Humidity resistance		

Applications

Securing wooden panels, plaster and plaster mouldings, PVC, brick or natural stone baseboards, skirting boards, tiles, etc.

Repairing or assembling carpentry requiring strong adhesion and an adhesive with high filling ability.

Instructions for use

Surface preparation:

Mating surfaces must be clean (free from dust or grease) and dry with no loose parts.

Application:

Cut the end of the tube or cartridge seal. In the case of a cartridge, screw the nozzle and cut it at an angle to the desired cross-section.

Apply dabs on one of the surfaces, place in the desired position and press lightly (to ensure an even distribution of the product).

Separate the two surfaces after pressing and air for 5 to 10 minutes (the exact time will depend on the ambient temperature) before placing the parts back in their final position. Secure the parts in position by pressing them firmly into place with a rubber mallet or by employing presses, sash clamps or pressure clips.

For minor adhesions or when high initial strength (sagging) is not required, it can be applied to one side in dabs and placed directly in the final position.

Dissolving and cleaning

When wet, this product can be easily removed using a cloth moistened with PASO ADHESIVE REMOVER or a universal solvent.

Once dry, the product can only be removed using mechanical means.

Storage

This product is flammable. If stored in its original closed container in accordance with the storage restrictions for flammable products, the product will be usable for at least 12 months.

It is recommended not to store the product below 5 °C. If the product reaches this temperature, it should be warmed at room temperature for 24 hours.

Safety precautions

Harmful if inhaled.
Flammable.
Hazardous to the aquatic environment.

Keep out of the reach of children.

More detailed instructions are given in the relevant product safety data sheet.

The user shall take ultimate responsibility for determining the final suitability of the product by prior testing for all types of application.

The information given in this Technical Data Sheet should never be considered as a specification of the product's properties.

We guarantee the uniformity of the properties of our products in all supplies. The recommendations and information published in this technical data sheet are based on our current knowledge and rigorous laboratory tests. Due to the many variations in each project's materials and conditions, we ask our customers to conduct their own tests of utility under the expected working conditions and following our general instructions. This will avoid any subsequent damage, for the consequences of which the company is not responsible.