

TECHNICAL DATA

Duct Tape

Product description

Ceys Duct Tape is a polyester-mesh reinforced polyethylene self-adhesive tape.

Its 3-layer technology means it is impermeable to water and air (polyethylene layer), has high strength (woven polyester mesh) and adheres to any surface (ultra-adherent elastomer adhesive).

Ceys Duct Tape is a super-strength multi-purpose tape to instantly and easily repair, fix, seal, bond and insulate.

Technical characteristics

Format	Silver colour	Black colour
5 m x 50 mm	✓	✓
10 m x 50 mm	✓	✓
25 m x 50 mm	✓	
50 m x 50 mm	✓	
Thickness	130 µm	
Tensile strength	20 kg/layer (width of tape)	
Hydraulic pressure resistance	Up to 4 bar	
Elongation at break	7%	
Adhesion (steel)	3 kg (width of tape)	
T _{application}	0°C up to +50°C	
T _{service}	-5°C up to +70°C	
UV resistance		

Applications

- Emergency repair of all kinds of objects, tools, etc.
- Strong, flexible joints between different materials.
- Temporary securing of objects, including to difficult substrates (e.g. carpet).
- Repairs to fabric tears or rips.
- Sealing pipes (water, air).
- Heavy-duty packaging for heavy objects.
- Air- and water-proofing and insulating.

Materials

Adheres perfectly to:

- Wood
- Plastic
- Metal
- Cardboard
- Leather
- Synthetic leather
- Canvas
- Rubber, etc.

Instructions for use

Surface preparation:

Mating surfaces must be clean (free from dust or grease) and dry.

Application:

Apply directly to surface and apply light pressure, avoiding air pockets.

For maximum-strength repairs, wrap several turns of Ceys Duct Tape around the break point, keeping the tape tight with each turn.

For sealing, insulating or repairing cracks and fissures, one layer of Ceys Duct Tape is sufficient. Even so, where possible, it is strongly recommended to apply Ceys Duct Tape to both sides of the crack for a better seal.

Designed to be easily torn by hand. No need for scissors to cut off a length of tape.

Dissolving and cleaning

This product can be removed by vigorously peeling away. Remove any residual adhesive with Paso Adhesive Remover.

Storage

Store the product in a cool, dry place in its original closed packaging at a temperature of between 5°C and 25°C. In its original packaging the product has a life of 36 months.

Safety precautions

Keep out of the reach of children.

This article falls within the definition of an **article** as per Regulation (EC) 1907/2006, **REACH**, and that, as specified in the Guidance on the Compilation of Safety Data Sheets published by **ECHA** (European Chemicals Agency), **no Safety Data Sheet is required for this product to be marketed.**

The user shall take ultimate responsibility for determining the final suitability of the product in all types of application.

The information given in this Technical Data Sheet should never be considered as a specification of the product's properties.

We guarantee the uniformity of the properties of our products in all supplies. The recommendations and information published in this technical data sheet are based on our current knowledge and rigorous laboratory tests. Due to the many variations in each project's materials and conditions, we ask our customers to conduct their own tests of utility under the expected working conditions and following our general instructions. This will avoid any subsequent damage, for the consequences of which the company is not responsible.